

FORM PTO-1390		U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE	ATTORNEY'S DOCKET NUMBER 4444-020
TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371			U.S. APPLICATION NO. (if known, see 37 CFR 1.5) <b>09/807620</b>
INTERNATIONAL APPLICATION NO. PCT/FR99/02469	INTERNATIONAL FILING DATE 12 October 1999 (12.10.99)	PRIORITY DATE CLAIMED 14 October 1998 (14.10.98)	
TITLE OF INVENTION A METHOD SWITCHING THE VIDEO COMPONENT(S) OF A FIRST DIGITAL, AUDIO-VISUAL PROGRAM ONTO THE VIDEO COMPONENTS OF A SECOND DIGITAL, VIDEO-AUDIO PROGRAM TO COMPENSATE THEIR PHASE SHIFT			
APPLICANT(S) FOR DO/EO/US Dominique CURET, Michel VEILLARD, Germain LOLIVIER, Therese GARAUULT, Gerard HELLEGOUARCH, Andre DOUTEAU, Stephanie RELIER and Gerard MADEC			
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:			
<ol style="list-style-type: none"> <li>1. <input checked="" type="checkbox"/> This is a <b>FIRST</b> submission of items concerning a filing under 35 U.S.C. 371.</li> <li>2. <input type="checkbox"/> This is a <b>SECOND</b> or <b>SUBSEQUENT</b> submission of items concerning a filing under 35 U.S.C. 371.</li> <li>3. <input type="checkbox"/> This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).</li> <li>4. <input checked="" type="checkbox"/> A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.</li> <li>5. <input checked="" type="checkbox"/> A copy of the International Application as filed (35 U.S.C. 371(c)(2)) <ol style="list-style-type: none"> <li>a. <input checked="" type="checkbox"/> is transmitted herewith (required only if not transmitted by the International Bureau).</li> <li>b. <input type="checkbox"/> has been transmitted by the International Bureau.</li> <li>c. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US)</li> </ol> </li> <li>6. <input checked="" type="checkbox"/> A English translation of the International Application into English (35 U.S.C. 371(c)(2)). <ol style="list-style-type: none"> <li>a. <input checked="" type="checkbox"/> is attached hereto</li> <li>b. <input type="checkbox"/> has been previously submitted under 35 U.S.C. 154 371 (c)(2)</li> </ol> </li> <li>7. <input type="checkbox"/> Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)) <ol style="list-style-type: none"> <li>a. <input type="checkbox"/> are transmitted herewith (required only if not transmitted by the International Bureau).</li> <li>b. <input type="checkbox"/> have been transmitted by the International Bureau.</li> <li>c. <input type="checkbox"/> have not been made; however, the time limit for making such amendment has NOT expired.</li> <li>d. <input type="checkbox"/> have not been made and will not be made.</li> </ol> </li> <li>8. <input type="checkbox"/> A English translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).</li> <li>9. <input type="checkbox"/> An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).</li> <li>10. <input type="checkbox"/> A English translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).</li> </ol>			
<b>Items 11. to 20. below concern other document(s) or information included:</b>			
<ol style="list-style-type: none"> <li>11. <input checked="" type="checkbox"/> An Information Disclosure Statement under 37 CFR 1.97 and 1.98.</li> <li>12. <input type="checkbox"/> An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.</li> <li>13. <input checked="" type="checkbox"/> A FIRST preliminary amendment.</li> <li>14. <input type="checkbox"/> A SECOND or SUBSEQUENT preliminary amendment.</li> <li>15. <input type="checkbox"/> A substitute specification.</li> <li>16. <input type="checkbox"/> A change of power of attorney and/or address letter.</li> <li>17. <input type="checkbox"/> A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821-1.825</li> <li>18. <input type="checkbox"/> A second copy of the published international application under 35 U.S.C. 154(d)(4)</li> <li>19. <input type="checkbox"/> A second copy of the English language translation of the international application under 35 U.S.C. 154(d)(4)</li> <li>20. <input type="checkbox"/> Other items or information.</li> </ol>			

09807620-071601

U.S. APPLIC. NO. (if known, see 37 CFR 1.5) <div style="font-size: 2em; font-weight: bold; margin-left: 50px;">09/807620</div>		INTERNATIONAL APPLICATION NO. PCT/FR99/02469		ATTORNEY'S DOCKET NUMBER 4444-020	
---	--	---	--	--------------------------------------	--

21. <input checked="" type="checkbox"/> The following fees are submitted: <b>Basic National Fee (37 CFR 1.492(a)(1)-(5)):</b> Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO ..... \$ 1000.00 International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO and JPO ..... \$ 860.00 International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO ..... \$ 710.00 International preliminary examination fee paid to USPTO (37 CFR 1.482) but all claims did not satisfy provisions of PCT Article 33(1)-(4) ..... \$ 690.00 International preliminary examination fee paid to USPTO (37 CFR 1.482) And all claims satisfied provisions of PCT Article 33(2)-(4) ..... \$ 100.00 <div style="text-align: right; margin-top: 10px;"><b>ENTER APPROPRIATE BASIC FEE AMOUNT =</b></div>				CALCULATIONS      PTO USE ONLY           <div style="border: 1px solid black; padding: 2px; margin-top: 10px;">\$      860.00</div>	
Surcharge of <b>\$130.00</b> for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(e)).				<div style="border: 1px solid black; padding: 2px;">\$      0.00</div>	
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE		
Total Claims	18      - 20 =		X \$18.00	\$      0.00	
Independent Claims	1      - 3 =		X \$78.00	\$      0.00	
Multiple dependent claim(s) (if applicable)			+ \$260.00	\$      0.00	
<b>TOTAL OF ABOVE CALCULATIONS =</b>				\$      860.00	
<input type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27. The fees indicated above are reduced by 1/2.				\$      0.00	
<b>SUBTOTAL =</b>				\$      860.00	
Processing fee of <b>\$130.00</b> for furnishing the English translation later than the <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(f)).				\$      0.00	
<b>TOTAL NATIONAL FEE =</b>				\$      860.00	
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property				\$      0.00	
<b>TOTAL FEES ENCLOSED =</b>				\$      860.00	
				Amount to be: refunded	\$
				charged	\$

a. ☐ A check in the amount of \$ XXX.XX to cover the above fees is enclosed.

b. ☐ Please charge my Deposit Account No. XXX in the amount of \$ XXX to cover the above fees. A duplicate copy of this sheet is enclosed.

c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 07-1337. A duplicate copy of this sheet is enclosed.

c. ☒ Fees are to be charged to a credit card **WARNING:** information on this form may be public. **Credit card information should not be included on this form.** Provide credit card information and authorization on PTO-2038.

**NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.**

SEND ALL CORRESPONDENCE TO:

Allan M. Lowe  
 LOWE HAUPTMAN GILMAN & BERNER, LLP  
 1700 Diagonal Road, Suite 310  
 Alexandria, VA 22314  
 (703) 684-1111

SIGNATURE  
 Allan M. Lowe  
 NAME  
 19,641  
 REGISTRATION NUMBER

Docket No.: 4444-020PATENT**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

In re Application of :  
 Dominique CURET et al :  
 Serial No. Not assigned : Group Art Unit: n/a  
 Filed: Herewith : Examiner: n/a  
 For: A METHOD SWITCHING THE VIDEO COMPONENT(S) OF A FIRST  
 DIGITAL, AUDIO-VISUAL PROGRAM ONTO THE VIDEO COMPONENTS  
 OF A SECOND DIGITAL, VIDEO-AUDIO PROGRAM TO COMPENSATE  
 THEIR PHASE SHIFT

**PRELIMINARY AMENDMENT**

Assistant Commissioner for Patents  
 Washington, D. C. 20231

Sir:

Prior to examination on the merits, please amend the claims as follows:

**IN THE CLAIMS:**

1. (Amended) A method of switching video component(s) of a first digital audio-visual program onto video component(s) of a second digital audio-visual program, each video component including in the order of presentation, an ordered sequence of pictures which are either Intra pictures (denoted by I) or predictive pictures (denoted by P) or bidirectional pictures (denoted by B), each Intra picture referring to no other picture, each predictive picture referring to the Intra picture or to the predictive picture

09/807620 071601

Serial No. sn

preceding it, each bidirectional picture being able to refer to two non-bidirectional pictures Intra or P, either to the Intra picture or to the predictive picture preceding it or to the Intra picture or the P picture following it, or to a combination of the two preceding or following Intra or predictive pictures,

the method comprising (a) switching at a switching time following the end of a picture of the first program after the switch command onto the picture of the video component of the second program which is present at said time, and (b) replacing, as seen in the order of transmission, each picture other than Intra of said second program component, where said latter picture is situated between the switching time and the beginning of the next Intra picture of said second program component, with a picture having the coding thereof being carried out independently of the picture data of the replaced picture and of the contents of the pictures to which the replacement picture refers.

2. (Amended) The method of claim 1, further including replacing (a) the information present in the second-program video component between the time at which the end of a picture of the first-program video component has been encountered after having received the switch command and the beginning of the first picture of the second program with (b) stuffing data.

Serial No. sn

3. (Amended) The method of claim 1, further including updating the time references of each replacement picture.

4. (Amended) The method of claim 1 further including retrieving the information relating to the minimum delay Vbv before it is possible to decode a picture from the replaced picture and moving the information relating to the minimum delay Vbv before it is possible to decode a picture from the replaced picture into each corresponding substitution picture unless it be equal to 'FFFF' in the other pictures of said second program component, in which latter case it assumes the value 'FFFF'.

5. (Amended) The method of claim 1 wherein the replacement pictures are included in a sequence of bidirectional B pictures all referring to the last predictive P picture of the first-program video component, and further including resetting to a zero value the motion estimating vectors of each of the bidirectional replacement pictures.

6. (Amended) The method of claim 5, wherein said replacement B pictures are interleaved pictures comprising a BOTTOM frame and a TOP frame which thereby are similar to digital television pictures and their predictions are field-based predictions, the TOP frames and the BOTTOM frames of said B replacement pictures

Serial No. sn

referring to the single BOTTOM frame of the last predictive picture P of the first-program video component.

7. (Amended) The method as of claim 1 wherein the replacement pictures are included in a sequence of pictures which as seen in the direction of transmission includes a predictive picture followed by one or more bidirectional pictures, the predictive replacement picture P referring to the last predictive picture P of the first-program video component and each of the bidirectional pictures B referring to said replacement picture P, and setting to a zero value the motion estimating vectors of each of the replacement pictures.

8. (Amended) The method of claim 1 wherein the replacement pictures are included in a sequence of pictures which includes, as seen in the direction of transmission, alternating predictive and bidirectional pictures, the first predictive replacement picture P referring to the last predictive picture P or Intra picture I of the first-program video component, then each following predictive replacement picture P referring to the predictive picture P which precedes it, and each bidirectional replacement picture B referring only to the predictive picture P which precedes it, the number of bidirectional pictures B between two predictive pictures P being equal to that encountered in the first-program video component, and

Serial No. sn

the motion estimating vectors of each replacement picture being set to a zero value.

9. (Amended) The method of claim 7 wherein said replacement pictures are frame pictures comprising a TOP frame and a BOTTOM frame which thereby are similar to a digital television picture and their predictions are field-based predictions, the TOP and BOTTOM frames of the first predictive replacement picture P referring to the single BOTTOM frame of the last predictive picture P or I of the first-program video component and the TOP and BOTTOM frames of the following bidirectional B or predictive P pictures referring to the BOTTOM frame of the first predictive replacement picture P.

10. (Amended) The method of claim 1 wherein the replacement pictures are included in a sequence of pictures which includes as seen in the order of transmission of a first picture which is an Intra picture, the other pictures being an alternation of bidirectional and predictive pictures, the first predictive replacement picture P referring to the Intra picture, then each following predictive replacement picture P referring to the predictive picture P which precedes it, and each bidirectional replacement picture B only referring to the predictive picture P or the Intra picture I which precedes it, the number of bidirectional pictures B between two predictive pictures P being equal to that

Serial No. sn

encountered in the first-program video component and setting to a zero value the motion estimating vectors of each replacement picture except for the Intra picture which lacks motion estimating vectors.

11. (Amended) The method of claim 10 wherein said replacement pictures are frame pictures comprising a TOP frame and a BOTTOM frame which thereby are pictures similar to those of digital television, and the predictions of the bidirectional pictures B and the predictive pictures P being field-based predictions, the TOP and the BOTTOM frames of the P or B replacement pictures which follow the picture I referring to the BOTTOM frame of the I or P replacement picture which precedes it.

12. (Amended) The method of claim 5 wherein the method is performed with a transmission system for transporting said pictures by transport packet streams, each transport packet stream including video components of the first and second programs, each transport packet TP including a payload unit start PUSI indicator which, when set at 1, indicates that said packet contains the beginning of a packetized elementary stream PES packet, the PES packets being aligned with the beginning payloads of the transport packets TP, each PES packet containing only one picture, certain transport packets in said transmission system being arranged to carry a



Serial No. sn

random access transport indicator RAI which, when set at 1, denotes that the next transport packet moving this component contains the first data of a video sequence, the method further comprising

determining the first transport packet TP of the first-program video component after the switch command, said packet comprising a random access indicator RAI set at 1 in order to determine the time of switching onto the second program,

switching onto said second-program video component and replacing the transport packets TP of this video component with stuffing transport packets until the appearance of the following transport packet TP of which the PUSI indicator is set at 1,

within this transport packet TP of which the PUSI indicator is set at 1 and if the RAI indicator is not set, replacing the PES packet header situated at the beginning of the payload with a reconstructed PES packet header,

Serial No. sn

starting with this transport packet and after the PES packet header, replacing the payload data of each transport packet of this component with the replacement picture data,

when all replacement picture data have been inserted into the payload of the video component transport packets TP, replacing the payload data of the following transport packets TP of the component with video stuffing until the appearance of the next transport packet of this second-program video component of which the PUSI indicator is set at 1, this transport packet TP excluded,

then restarting the preceding stage from this transport packet TP with the PUSI indicator set at 1 until the appearance of the next transport packet TP of the second-program video component of which the random access indicator RAI is set at 1, this transport packet excluded,

setting the discontinuity indicator DI at 1 on this packet with random access indicator RAI which corresponds to the end of replacement and to the effective beginning of the second program video.

Serial No. sn

13. (Amended) The method of claim 12, further including denoting scrambled transport packets TP in clear while setting the control field of transport scrambling control TSC at the binary value 00.

14. (Amended) The method of claim 5, wherein the method is performed with a transmission system for importing said pictures by transport packet streams, each transport packet stream including the video components of the first and second programs, each transport packet TP comprising a payload unit start indicator PUSI which, when set at 1, indicates that said packet contains the beginning of packetized elementary stream PES packet, the PES packets being aligned with the beginning of the transport packet TP payloads, each PES packet containing only one picture, said transmission system being such that certain transport packets are arranged to carry a random access transport indicator RAI which, when set at 1, indicates that the next transport packet moving this component contains the first data of a video sequence,

the method further comprising

determining the first transport packet TP of the first-program video component present after the switch command and including a random access indicator RAI set at 1 in

Serial No. sn

order to determine the time of switching onto the second program,

switching onto said second-program video component and replacing the transport packets TP of said video components with stuffing transport packets until the appearance of the following transport packet TP of which the PUSI indicator is set at 1,

if the RAI indicator is set based on this transport packet and after the PES packet header, then replacing the payload data of each transport packet of this component with the replacement picture data, and when all the replacement picture data have been inserted in the payload of the video component transport packets TP, substituting the payload data of the following transport packets TP of the component with video stuffing until the appearance of the next transport packet of this second-program video component of which the PUSI indicator is set at 1, this transport packet TP being excluded,

then restarting the preceding stage on the basis of this transport packet TP with the PUSI indicator set at 1 until the appearance of the next transport packet TP of

Serial No. sn

the second-program video component of which the random access indicator RAI is set at 1, this transport packet being excluded, and

setting the discontinuity indicator DI at 1 on this packet with the random access indicator RAI, which corresponds to the end of replacement and to the effective beginning of the second program video.

15. (Amended) The method of claim 12 wherein for the case of one or both video components being devoid of a random access indicator RAI set in the transport stream, the following steps are performed:

determining the transport packet TP of the video component of the stream(s) without RAI indicator of which the PUSI indicator is set at 1 and of which the payload data begin with a video sequence header,

searching for the sequence header following the switch command,

setting the discontinuity index in the determined transport packet TP if the latter comprises an adaptation field AF with

Serial No. sn

a program clock reference PCR when the component carries the program clock,

or if the determined transport packet TP does not include an adaptation field AF or if the program clock carrying component is involved and the adaptation field AF lacks a clock reference PCR, replacing the determined transport packet TP with a specific transport packet TP called the inserted transport packet, and shifting the replaced transport packet TP as well as the following transport packets TP of this video component in the transport stream until one of them can be inserted into a stuffing transport packet TP.

16. (Amended) The method of claim 15, wherein the inserted transport packet includes the following characteristics:

the PUSI indicator is set at 0,

the status of the continuity counter COMP is set at that of the continuity counter of the initial transport packet TP less 1,

Serial No. sn

the control field AFC of the adaptation field AF is set at the binary value 10, denoting the presence of an adaptation field AF in this transport packet TP, but no payload,

the discontinuity indicator DI situated in the adaptation field AF is set at 1,

if the video component carries the program clock, a program clock reference PCR calculated on the basis of the preceding clock reference(s) PCR of the same component is set into the adaptation field.

17. (Amended) The method of claim 15, for the case of a presentation stamp PTS being present in the header of the PES packet including the sequence header, further including pre-processing the setting of the random access indicator RAI, said transport packet TP being inserted to set the random access indicator RAI then includes the following characteristics:

the PUSI indicator is set at 0,

Serial No. sn

the status of the continuity counter COMP is set at that of the continuity counter of the initial transport packet TP, less 1,

the control field AFC of the adaptation field AF is set at the binary value 10 denoting that an adaptation field AF is present in this transport packet TP but no payload,

the RAI indicator situated in the adaptation field AF is set at 1,

the discontinuity indicator DI situated in the adaptation field is set,

if the video component carries a program clock, a program clock reference PCR calculated on the basis of the preceding clock reference(s) PCR of the same component is moved into the adaptation field AF.

18. (Amended) The method of claim 15, for the case of a presentation stamp being absent from the header of the PES packet containing the sequence header, further including pre-processing the setting of the RAI indicator, modifying the initial transport packet TP in such a way that its PUSI indicator is set at 0 and the



Serial No. sn

useful data are eliminated from the PES packet header, said transport packet TP inserted to set the RAI indicator then including the following features:

the PUSI indicator is set at 1,

the status of the continuity counter COMP is set at that of the continuity counter of the transport packet TP less 1,

the control field AFC of the adaptation field AF is set at the binary value 11 to denote that an adaptation field AF and a payload are present in this transport packet,

the adaptation field AF comprises an RAI indicator set at 1,

the discontinuity is set at 1 on this packet with RAI indicator,

a program clock reference PCR calculated on the basis of the preceding clock reference(s) is set in the adaptation field AF if the video component carries the program clock,

Serial No. sn

a presentation stamp PTS is calculated and moved into the payload of this packet,

the PES packet header which was in the replaced transport packet TP is shifted into the payload of this inserted transport packet TP and in case of the absence of the presentation stamp PTS from the PES packet header, this PTS stamp shall be calculated and set in the header data of this PES packet.

Serial No. sn

#### ABSTRACT OF THE DISCLOSURE

The video component(s) of a digital audio-visual first program are switched onto the video components of a second digital, audio-visual program by (1) switching onto the video component of the second program, subsequent to the switch command and to the end of a picture of the first program, and (2) replacing, as seen in the order of transmission, each non Intra picture of the component of a second program, with a picture having coding performed independently of (a) the picture data of the replaced picture and (b) of the contents of the pictures to which it refers until the beginning of the next Intra picture of the component of the second program.

Serial No. sn

R E M A R K S

Multiple dependent claims have been eliminated to avoid payment of the multiple dependent claim fee. The abstract of the disclosure and claims have also been amended to conform with U.S. practice, without any effect on the patentability thereof. Entry is in order.

To the extent necessary, a petition for an extension of time under 37 C.F.R. 1.136 is hereby made. Please charge any shortage in fees due in connection with the filing of this paper, including extension of time fees, to Deposit Account 07-1337 and please credit any excess fees to such deposit account.

Respectfully submitted,

LOWE HAUPTMAN GILMAN & BERNER, LLP



Allan M. Lowe  
Registration No. 19,641

1700 Diagonal Road, Suite 310  
Alexandria, Virginia 22314  
(703) 684-1111/FAX: (703) 518-5499  
AML:cjf  
Date: April 13, 2001

Serial No. sn

MARKED UP VERSION SHOWING CHANGES

1. A method of [for] switching [the] video component(s) of a first digital audio-visual program onto [the] video component(s) of a second digital audio-visual program, each video component including [being constituted, as seen] in the order of presentation, [by] an ordered sequence of pictures which are either Intra pictures (denoted by I) or predictive pictures (denoted by P) or bidirectional pictures (denoted by B), each Intra picture referring to no other picture, each predictive picture referring to the Intra picture or to the predictive picture preceding it, each bidirectional picture being able to refer to two non-bidirectional pictures Intra or P, either to the Intra picture or to the predictive picture preceding it or to the Intra picture or the P picture following it, or to a combination of the two preceding or following Intra or predictive pictures,

[characterized in that]

the [said] method comprising [consists in] (a) switching at a switching time following the end of a picture of the first program after the switch command onto the picture of the video component of the second program which is present at said time and (b) [in] replacing, as seen in the order of transmission, each picture other than Intra of said second program component, where said latter picture is situated between the switching time and the beginning of

Serial No. sn

the next Intra picture of said second program component, with a picture having [of which] the coding thereof being [is] carried out independently of the picture data of the replaced picture and of the contents of the pictures to which the replacement picture refers.

2. The [M]method of [as claimed in] claim 1, including replacing (a) [characterized in that] the information present in the second-program video component between the time at which the end of a picture of the first-program video component has been encountered after having received the switch command and the beginning of the first picture of the second program [is replaced] with (b) stuffing data.

3. The [M]method of [as claimed in either] of claim[s] 1 [and 2, characterized in that] further including updating the time references of each replacement picture[ are updated].

4. The [M]method [as claimed in one of the above claims,] of claim 1 further including retrieving the information relating to the minimum delay Vbv before it is possible to decode a picture from the replaced picture [characterized in that the information relating to the minimum delay Vbv before it is possible to decode a picture is retrieved from the replaced picture] and moving the

Serial No. sn

information relating to the minimum delay Vbv before it is possible to decode a picture from the replaced picture [moved] into each corresponding substitution picture unless it be equal to 'FFFF' in the other pictures of said second program component, in which latter case it assumes the value 'FFFF'.

5. The [M]method of [as claimed in one of the above claims, characterized in that] claim 1 wherein the replacement pictures are included in [constitute] a sequence of bidirectional B pictures all referring to the last predictive P picture of the first-program video component, and further including resetting to a zero value the motion estimating vectors of each of the bidirectional replacement pictures[ being set to a zero value].

6. The [M]method of [as claimed in] claim 5, wherein [characterized in that] said replacement B pictures are interleaved pictures comprising a BOTTOM frame and a TOP frame which thereby are similar to digital television pictures and their predictions are field-based predictions, the TOP frames and the BOTTOM frames of said B replacement pictures referring to the single BOTTOM frame of the last predictive picture P of the first-program video component.

Serial No. sn

7. The [M]method of [as claimed in] claim 1 [through 4, characterized in that] wherein the replacement pictures are included in [constitute] a sequence of pictures which as seen in the direction of transmission includes [consists of] a predictive picture followed by one or more bidirectional pictures, the predictive replacement picture P referring to the last predictive picture P of the first-program video component and each of the bidirectional pictures B referring to said replacement picture P, and setting to a zero value the motion estimating vectors of each of the replacement pictures[ being set to a zero value].

8. The [M]method of [as claimed in] claim 1 [through 4, characterized in that] wherein the replacement pictures are included in [constitute] a sequence of pictures which include [consists], as seen in the direction of transmission, [of] alternating predictive and bidirectional pictures, the first predictive replacement picture P referring to the last predictive picture P or Intra picture I of the first-program video component, then each following predictive replacement picture P referring to the predictive picture P which precedes it, and each bidirectional replacement picture B referring only to the predictive picture P which precedes it, the number of bidirectional pictures B between two predictive pictures P being equal to that encountered in the



Serial No. sn

first-program video component, and the motion estimating vectors of each replacement picture being set to a zero value.

9. The [M]method [as claimed in either] of claims 7 [and 8, characterized in that] wherein said replacement pictures are frame pictures comprising a TOP frame and a BOTTOM frame which thereby are similar to a digital television picture and their predictions are field-based predictions, the TOP and BOTTOM frames of the first predictive replacement picture P referring to the single BOTTOM frame of the last predictive picture P or I of the first-program video component and the TOP and BOTTOM frames of the following bidirectional B or predictive P pictures referring to the BOTTOM frame of the first predictive replacement picture P.

10. The [M]method of [as claimed in] claim 1 [through 4, characterized in that] wherein the replacement pictures are included in [constitute] a sequence of pictures which consists as seen in the order of transmission of a first picture which is an Intra picture, the other pictures being an alternation of bidirectional and predictive pictures, the first predictive replacement picture P referring to the Intra picture, then each following predictive replacement picture P referring to the predictive picture P which precedes it, and each bidirectional replacement picture B only referring to the predictive picture P or

Serial No. sn

the Intra picture I which precedes it, the number of bidirectional pictures B between two predictive pictures P being equal to that encountered in the first-program video component, and setting to a zero value the motion estimating vectors of each replacement picture [being set to a zero value] except for the Intra picture which lacks motion estimating vectors.

11. The [M]method of [as claimed in] claim 10 wherein [, characterized in that] said replacement pictures are frame pictures comprising a TOP frame and a BOTTOM frame which thereby are pictures similar to those of digital television, and the predictions of the bidirectional pictures B and the predictive pictures P being field-based predictions, the TOP and the BOTTOM frames of the P or B replacement pictures which follow the picture I referring to the BOTTOM frame of the I or P replacement picture which precedes it.

12. The [M]method [as claimed in one] of claim[s] 5 [through 11, which is implemented in] wherein the method is performed with a transmission system for transporting [wherein] said pictures by transport packet streams, each transport packet stream including [constituting] video components of the first and second programs, [are transported by transport packet streams,] each transport packet TP including [being fitted with] a payload unit start PUSI

Serial No. sn

indicator which, when set at 1, indicates that said packet contains the beginning of a packetized elementary stream PES packet, the PES packets being aligned with the beginning [the] payloads of the transport packets TP, each PES packet containing only one picture, [wherein said transmission system] certain transport packets [are intended] in said transmission system being arranged to carry [transport information such as] a random access transport indicator RAI which, when set at 1, denotes that the next transport packet moving this component contains the first data of a video sequence, the method further comprising

[characterized in that  
said method consists]

[-- ]determining the first transport packet TP of the first-program video component after the switch command, [ ,] said packet comprising a random access indicator RAI set at 1 in order to determine the time of switching onto the second program,

[-- ]switching onto said second-program video component and replacing the transport packets TP of this video component with stuffing transport packets until the appearance of the following transport packet TP of which the PUSI indicator is set at 1,

Serial No. sn

[-- ]within this transport packet TP of which the PUSI indicator is set at 1 and if the RAI indicator is not set, replacing the PES packet header situated at the beginning of the payload with a reconstructed PES packet header,

[-- ]starting with this transport packet and after the PES packet header, replacing the payload data of each transport packet of this component with the replacement picture data, [and]

when all replacement picture data have been inserted into the payload of the video component transport packets TP, replacing the payload data of the following transport packets TP of the component with video stuffing [such as '00 octets] until the appearance of the next transport packet of this second-program video component of which the PUSI indicator is set at 1, this transport packet TP excluded,

[-- ]then restarting the preceding stage from this transport packet TP with the PUSI indicator set at 1 until the appearance of the next transport packet TP of the second-program video component of which the random access indicator RAI is set at 1, this transport packet excluded,

Serial No. sn

[-- ]setting the discontinuity indicator DI at 1 on this packet with random access indicator RAI which corresponds to the end of replacement and to the effective beginning of the second program video.

13. The [M]method of [as claimed in] claim 12, further including [characterized in that when the transport packets TP are scrambled, this method consists in] denoting scrambled transport packets TP [them] in clear while setting the control field of transport scrambling control TSC at the binary value 00.

14. The [M]method of [as claimed in one of] claim[s] 5 [through 11 and being implemented in] wherein the method is performed with a transmission system for transporting [wherein] said pictures by transport packet streams, each including [constituting] the video components of the first and second programs, [are moved by transport packet streams,] each transport packet TP comprising a payload unit start indicator PUSI, which when set at 1, indicates [denotes] that said packet contains the beginning of packetized elementary stream PES packet, the PES packets being aligned with the beginning of the transport packet TP payloads, each PES packet containing only one picture, said transmission system being such that certain transport packets are arranged [are intended] to carry [transport information such as] a

Serial No. sn

random access transport indicator RAI which, when set at 1, indicates that the next transport packet moving this component contains the first data of a video sequence,

[characterized in that ]

the [said] method further comprising[ consists in]:

[-- ]determining the first transport packet TP of the first-program video component present after the switch command and including [comprising] a random access indicator RAI set at 1 in order to determine the time of switching onto the second program,

[-- ]switching onto said second-program video component and replacing the transport packets TP of said video components with stuffing transport packets until the appearance of the following transport packet TP of which the PUSI indicator is set at 1,

[-- ]if the RAI indicator is set based on this transport packet and after the PES packet header, then replacing the payload data of each transport packet of this component with the replacement picture data, and when all the replacement picture data have been inserted in the payload of the video component transport packets TP,

Serial No. sn

substituting the payload data of the following transport packets TP of the component with video stuffing [such as '00 octets] until the appearance of the next transport packet of this second-program video component of which the PUSI indicator is set at 1, this transport packet TP being excluded,

[-- ]then restarting the preceding stage on the basis of this transport packet TP with the PUSI indicator set at 1 until the appearance of the next transport packet TP of the second-program video component of which the random access indicator RAI is set at 1, this transport packet being excluded, and

[-- ]setting the discontinuity indicator DI at 1 on this packet with the random access indicator RAI, which corresponds to the end of replacement and to the effective beginning of the second program video.

15. The [M]method of [as claimed in one of] claim[s] 12[, 13 or 14,] wherein for the case of one or both video components being devoid of a random access indicator RAI set in the transport stream, the following steps are performed[ characterized by consisting in]:

Serial No. sn

[-- ]determining the transport packet TP of the video component of the stream(s) without RAI indicator of which the PUSI indicator is set at 1 and of which the payload data begin with a video sequence header,

[-- ]searching for the sequence header following the switch command,

[-- ]setting the discontinuity index in the determined transport packet TP if the latter comprises an adaptation field AF with a program clock reference PCR when the component carries the program clock,

[-- ]or if the determined transport packet TP does not comprise an adaptation field AF or if the program clock carrying component is involved and the adaptation field AF lacks a clock reference PCR, replacing the determined transport packet TP with a specific transport packet TP called the inserted transport packet, and shifting the replaced transport packet TP as well as the following transport packets TP of this video component in the transport stream until one of them can be inserted into a stuffing transport packet TP.



Serial No. sn

16. The [M]method of [as claimed in] claim 15[, characterized in that] wherein the inserted transport packet includes [exhibits] the following characteristics:

[-- ]the PUSI indicator is set at 0,

[-- ]the status of the continuity counter COMP is set at that of the continuity counter of the initial transport packet TP less 1,

[-- ]the control field AFC of the adaptation field AF is set at the binary value 10, denoting the presence of an adaptation field AF in this transport packet TP, but no payload,

[-- ]the discontinuity indicator DI situated in the adaptation field AF is set at 1,

[-- ]if the video component carries the program clock, a program clock reference PCR calculated on the basis of the preceding clock reference(s) PCR of the same component is set into the adaptation field.

Serial No. sn

17. The [M]method of [as claimed in] claim 15, for the case of a presentation stamp PTS being present in the header of the PES packet including [containing] the sequence header, further including [characterized in that it consists in] pre-processing the setting of the random access indicator RAI, [ , ] said transport packet TP being inserted to set the random access indicator RAI then includes [exhibiting] the following characteristics:

[-- ]the PUSI indicator is set at 0,

[-- ]the status of the continuity counter COMP is set at that of the continuity counter of the initial transport packet TP, less 1,

[-- ]the control field AFC of the adaptation field AF is set at the binary value 10 denoting that an adaptation field AF is present in this transport packet TP but no payload,

[-- ]the RAI indicator situated in the adaptation field AF is set at 1,

[-- ]the discontinuity indicator DI situated in the adaptation field is set,

Serial No. sn

[-- ]if the video component carries the program clock, a program clock reference PCR calculated on the basis of the preceding clock reference(s) PCR of the same component is moved into the adaptation field AF.

18. The [M]method of [as claimed in] claim 15, for the case of a [the] presentation stamp being absent from the header of the PES packet containing the sequence header, further including [characterized in that it consists in] pre-processing the setting of the RAI indicator, [in that] modifying the initial transport packet TP [is modified] in such a way that its PUSI indicator is set at 0 and the useful data are eliminated from the PES packet header, said transport packet TP inserted to set the RAI indicator then including [exhibiting] the following features:

[-- ]the PUSI indicator is set at 1,

[-- ]the status of the continuity counter COMP is set at that of the continuity counter of the transport packet TP less 1,

[-- ]the control field AFC of the adaptation field AF is set at the binary value 11 to denote that an adaptation field AF and a payload are present in this transport packet,

Serial No. sn

[-- ]the adaptation field AF comprises an RAI indicator set at 1,

[-- ]the discontinuity is set at 1 on this packet with RAI indicator,

[-- ]a program clock reference PCR calculated on the basis of the preceding clock reference(s) is set in the adaptation field AF if the video component carries the program clock,

[-- ]a presentation stamp PTS is calculated and moved into the payload of this packet,

[-- ]the PES packet header which was in the replaced transport packet TP is shifted into the payload of this inserted transport packet TP and in case of the absence of the presentation stamp PTS from the PES packet header, this PTS stamp shall be calculated and set in the header data of this PES packet.

Serial No. sn

ABSTRACT OF THE DISCLOSURE

T[he present invention relates to a method for switching t]he video component(s) of a digital audio-visual first program are switched onto the video components of a second digital, audio-visual program[.] by

[ In the invention, said method is characterized in that it consists in] (a) switching onto the video component of the second program, subsequent to the switch command and to the end of a picture of the first program, and (b) [in] replacing, as seen in the order of transmission, each non Intra picture of said component of a [said] second program, with a picture having [of which the] coding performed [is carried out] independently of (a) the picture data of the replaced picture and (b) of the contents of the pictures to which it refers until the beginning of the next Intra picture of the [said] component of the [said] second program.



## DEMANDE INTERNATIONALE PUBLIÉE EN VERTU DU TRAITE DE COOPERATION EN MATIÈRE DE BREVETS (PCT)


(51) Classification internationale des brevets <sup>7</sup> : <b>H04N 7/58, 5/265</b>		(11) Numéro de publication internationale: <b>WO 00/22835</b>
<b>A1</b>		(43) Date de publication internationale: 20 avril 2000 (20.04.00)
(21) Numéro de la demande internationale: PCT/FR99/02469		(74) Mandataire: MAILLET, Alain; Cabinet Le Guen & Maillet, 38, rue Levassasseur, Boîte postale 91, F-35802 Dinard Cedex (FR).
(22) Date de dépôt international: 12 octobre 1999 (12.10.99)		(81) Etats désignés: JP, US, brevet européen (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).
(30) Données relatives à la priorité: 98/12973 14 octobre 1998 (14.10.98) FR		Publiée Avec rapport de recherche internationale. Avant l'expiration du délai prévu pour la modification des revendications, sera republiée si des modifications sont reçues.
(71) Déposants (pour tous les Etats désignés sauf US): FRANCE TELECOM SA [FR/FR]; 6, place d'Alleray, F-75015 Paris (FR). TELEDIFFUSION DE FRANCE SA [FR/FR]; 10, rue d'Oradour-sur-Glane, F-75015 Paris (FR).		
(72) Inventeurs; et		
(75) Inventeurs/Déposants (US seulement): CURET, Dominique [FR/FR]; 38, rue Lariboisière, F-35235 Thorigné Fouillard (FR). VEILLARD, Michel [FR/FR]; 69, rue Mozart, F-35170 Bruz (FR). LOLIVIER, Germain [FR/FR]; 3, square de Tanouarn, F-35700 Rennes (FR). GARAUULT, Thérèse [FR/FR]; 107, rue F. Benoît, F-35136 St Jacques de la Lande (FR). HELLEGOUARCH, Gérard [FR/FR]; 33, rue de la Rabine, F-35510 Cesson-Sévigne (FR). DOUTEAU, André [FR/FR]; 10, rue de Turgé, F-35310 Chavagne (FR). RELIER, Stéphanie [FR/FR]; 28, square Fernand Labori, F-35700 Rennes (FR). MADEC, Gérard [FR/FR]; La Brosse, F-35250 Chasne-sur-Illet (FR).		

(54) Title: METHOD FOR SWITCHING VIDEO COMPONENT(S) OF A FIRST AUDIO-VISUAL DIGITAL PROGRAMME ON THE VIDEO COMPONENT(S) OF A SECOND AUDIO-VISUAL DIGITAL PROGRAMME TO COMPENSATE PHASE-SHIFT

(54) Titre: PROCEDE DE BASCULEMENT DE LA OU DES COMPOSANTES VIDEO D'UN PREMIER PROGRAMME AUDIOVISUEL NUMERIQUE SUR LA OU LES COMPOSANTES VIDEO D'UN SECOND PROGRAMME AUDIOVISUEL NUMERIQUE POUR COMPENSER LEUR DEPHASAGE

## (57) Abstract

The invention concerns a method for switching video component(s) of a first audio-visual digital programme on the video component(s) of a second audio-visual digital programme, characterised in that it consists in switching on the second programme video component after the switching command and after the end of a picture of the first programme and in substituting, in transmission order, for each non-Intra-coded picture of said second programme a picture whereof the coding is produced independently of the substituted picture image data and of the contents of the images whereto it refers until the next Intra-coded picture of said component of said second programme begins.



GOP...GROUPE D'IMAGES

## (57) Abrégé

La présente invention concerne un procédé de basculement de la ou des composantes vidéo d'un premier programme audiovisuel numérique sur la ou les composantes vidéo d'un second programme audiovisuel numérique. Selon l'invention, ledit procédé est caractérisé en ce qu'il consiste à basculer sur la composante vidéo du second programme après la commande de basculement et après la fin d'une image du premier programme et à substituer, dans l'ordre de transmission, à chaque image non Intra de ladite composante dudit second programme une image dont le codage est réalisé indépendamment des données d'image de l'image substituée et des contenus des images auxquelles elle se réfère jusqu'au commencement de la prochaine image Intra de ladite composante dudit second programme.

	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2423	2424	2425	2426	2427	2428	2429	2430	2431	2432	2433	2434	2435	2436	2437	2438	2439	2440	2441	2442	2443	2444	2445	2446	2447	2448	2449	2450	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

[005]       The audio and video portions of the MPEG-2 standard described how to digitally code the audio and video data. The system portion of

the MPEG-2 standard specifies that resultant compressed elementary streams are configured as elementary stream packets termed packetized elementary streams (PES) packets containing video data. These PES packets may be of fixed or variable size.

[006] In non restrictive manner the description below discusses the use of variable-size, video PES packets , each PES packet containing a single picture and where called for sequence headers or headers of group of pictures GOP, the pictures being aligned at the beginning of the PES packet. The PES packets moving the same elementary stream are identified by a stream identifier called the stream Id.

[007] The system MPEG-2 standard indicates that the PES packets (video, audio or data) may be multiplexed for local use for instance with signalization PES packets. Such a multiplex may be stored in the kind of disks known as DVD (digital versatile disk) for instance if a program MPEG-2 syntax is involved.

[008] According to the system MPEG-2 standard, the elementary stream configured as PES packets next may be cut into fixed-size packets called transport packets (TP). Such a fixed-size packet is identified by a packet identifier (PID). A stream of PES packets having the same stream ID can only be moved in transport packets having the same packet identifier PID. The transport packets moving a particular elementary stream (and the PES packets having divided this elementary stream a first time) can be multiplexed with other transport packets TP moving other elementary streams, and furthermore also including transport



packets TP containing the signalization. These multiplexes of transport packets TP then are available for transmission: it involves the transport MPEG-2 syntax.

[009] The system portion of MPEG-2 therefore relates to two syntaxes, the MPEG-2 program syntax and the MPEG-2 transport syntax. The MPEG-2 system syntax is generic in the sense that these two syntaxes can be converted one into the other and in that they apply to two very different applications: storing an MPEG-2 program and transmitting one or more MPEG-2 transport programs. One of the applications of the invention relates to these two syntaxes.

[010] The video portion of the video MPEG-2 standard relates to three kinds of pictures:

-- the so-called I pictures (intra coded) that do not refer to any other picture; these are the pictures with a moderate compression ratio; their coding does not entail using procedures of motion estimates,

-- the P pictures (predictive coded pictures) which are coded pictures using prediction procedures estimating motion based on a preceding picture which may be a type I or a type P picture,

-- the B pictures (bidirectional predictive-coded pictures) which are coded using prediction procedures of motion

estimates based on a preceding picture (as regards display, it is called forward prediction) and/or a future picture (as regards display, this is a back prediction) which are of the I or P type.

[011] The video MPEG-2 standard sets up six hierarchy levels for the syntax of an elementary video stream: the sequence, the group of pictures GOP which is the only optional level, the picture (type I, P or B), the picture slice, the macroblock and the block.

[012] A video sequence begins with a sequence header which is followed by one or more sets of pictures. According to the MPEG-2 standard, these sets of pictures may be configured in (optional) groups of pictures GOP. A group of pictures GOP is characterized by a header of group of pictures GOP situated before the pictures. In the order of transmission, a group of pictures GOP begins with a (mandatory) I picture followed in a rigorous order by a certain number of bidirectional B pictures and predictive P pictures.

[013] The conventional size of the group of pictures GOP being 12 pictures, the program video component consists of strings of sequences at one group of pictures GOP per sequence. In loose manner hereafter, a group of pictures GOP shall be called a sequence header followed by a 12-picture group of pictures GOP or by several smaller groups of pictures GOP.

[014] The pictures comprise a header and data consisting of a certain number of slices. One slice reconfigures several continuous macroblocks in the picture. In conventional (4:2:0 format) digital television, a macroblock is the combination of four luminance blocks, one block with a first chrominance component for the same pixels and one block of a second chrominance component also for the same pixels. One block contains the data of eight by eight squares of pixels.

[015] The illustrative application of the invention described further below remains within the scope of the MPEG-2 transport standard. This implementation relates to chaining different television programs. A first program selected from a given number of programs of a first multiplex is to be switched onto a second program selected from a given number of programs from a second multiplex and, as called for later, to switch again the second program onto the first one.

[016] These operations involve two same-syntax multiplexes (for instance MPEG-2 transport syntax or MPEG-2 program syntax) which are coded in real time or are retrieved from a storage system. The illustrative implementation of the invention described further below relates to the transport MPEG-2 but operations carried out at the elementary level and at the level of the PES packets are directly applicable to the program MPEG-2 standard.

[017] In particular reference is made to the patent document WO 98 32 281 A which describes a switching method based on compressed digital stream data such as the MPEG transport streams. In particular the

streams implemented in the invention described in said patent document are fitted with at least one stream entry point and at least one exit point identifying an appropriate exit point of this stream. Accordingly a main stream is switched at its output point onto the entry point of another stream. Furthermore an exit point of a video stream in general is the end of the last video transport packet of the stream. As regards the entry point, it is generally the beginning of the first transport packet of the stream under consideration. A stream between an entry point and an exit point is called a segment of which the first picture is a fixed picture and the second picture does not refer to a picture before the entry point. Also, the last segment picture in the order of presentation cannot be a B picture.

[018] It is understood in the light of the above that by appropriately selecting the input and output points, a main stream can be switched onto a segment and that this switching is carried out without a visible defect appearing in the presented picture.

[019] Nevertheless, as already cited in the above cited patent document, commercial television may deliberately generate streams lacking exit points, so that switching based on these streams must entail defects. Also someone using such a system must be able to control the source of the stream to which the switching is applied in order to meet the above constraints: entry point, first and second pictures, last picture. The applications cited in the above patent document are all carried out in a studio which therefore controls the

stream which shall be switched. In some applications, however, for instance at the head of a radio station, such may not be the case because the two sources are part of the television production channels.

[020] Moreover there are few manufacturers of the MPEG-2 coders who offer means implementing these entry and exit points.

[021] This kind of application raises a major problem in that the video components being switched one onto the other will not be necessarily synchronized. If not synchronized, they exhibit a phase difference due to processes taking place at different levels:

-- still at the elementary video level: the video scenes compressed by each video coder may exhibit different structures (picture sizes, structures of the groups of pictures, etc.),

-- regarding the PES packets: the packaging mode of the compressed pictures in the PES packets may differ from one component to the next,

-- as regards the transport packets TP: the advance or delay caused by the jitter of the transport packets within which the PES packets are being moved.

[022] Within the scope of the present invention, the phase differences at the elementary level assume foremost importance. As regards the PES packets, it will suffice to handle the case of one PES packet containing a single picture. On the other hand the jitter of the transport packets is ignored.

[023] Given the phase shift of the video coders, the end of a sequence or of a group of pictures GOP of the first program may be located anywhere in the video of the second program, for instance in the progress of an arbitrary picture. Therefore the next beginning picture may be a bidirectional B picture or a predictive P picture which refer to other pictures of the second program preceding switching and which were not transmitted because at that time the transmission did apply to the first program pictures. The result is improper decoding and defects in the displayed pictures that may last more or less depending on the magnitude of the phase difference between the two video components.

[024] In order to compensate this phase difference, one simple solution would be to delay the second program, entailing a storage having the capacity of a group of pictures GOP for each second-program video component. However this solution entails applying a permanent delay to the second program. Also this solution will be difficult to apply if the second program is scrambled.

AMENDED SHEET

[025] Therefore the objective of the present invention is to propose a method allowing solving the above cited phase difference problem and precluding delaying the second program.

[026] For that purpose a method of the invention switching the video component(s) of a first digital, audio-visual program onto the video component(s) of a second, digital audio-visual program is characterized in that the switching takes place after the command to switch onto the second-program video component and after the end of a picture of the first program and in replacing, in the order of transmission, each picture other than an Intra picture of said component of said second program with a picture which is coded independently of the picture data of the replaced picture and of the contents of the pictures to which it refers until the beginning of the next Intra picture of said component of the said second program.

[027] In another feature of the invention, its method consists in replacing the data present in the second-program video component between the time when the end of a picture of the first-program video component has been encountered after having received the switch command and the beginning of the first picture of the second program with stuffing data.

[028] In another feature of the invention, the time references of each replacement picture are updated.

[029] I another feature of the invention, the data relating to the expected minimum delay before it is feasible to decode a picture (Vbv delay) is retrieved from the replaced picture and positioned in each corresponding replacement picture unless it be different from 'FFFF in the other pictures of said component of said second program and in this case assuming the value 'FFFF.

[030] In a first implementation variation of the method of the invention, the replacement pictures constitute a sequence of bidirectional B pictures all referring to the last predictive picture P of the first-program video component, the motion estimating vectors of each bidirectional substitution picture B being set to a zero value. Said replacement pictures B for instance are interleaved pictures comprising a BOTTOM frame and a TOP frame which as a result are similar to digital television pictures and their predictions are field-based predictions. In this case the TOP frames and the BOTTOM frames of said B replacement pictures refer to the sole BOTTOM frame of the last predictive P picture of the first-program video component.

[031] In a second variation of implementation of the method of the invention, the replacement pictures constitute a sequence of pictures which, in the order of transmission, are a predictive picture followed by one or more bidirectional pictures, the predictive replacement picture P referring to the last predictive picture P of the first-program video component and each of the bidirectional B pictures referring to said predictive replacement picture P, the motion



estimating vectors of each of the substitution pictures being set to a zero value.

[032] In another mode of implementing the method of the present invention, the replacement pictures constitute a sequence of pictures which, in the order of transmission, consists alternating predictive and bidirectional pictures, the first predictive replacement picture referring to the last predictive picture P or I picture of the first-program video component, then each following replacement predictive picture P referring to the predictive P picture preceding it, and each bidirectional replacement picture B only referring to the predictive P picture which precedes it, the number of bidirectional B pictures between two predictive P pictures being equal to the number encountered in the first-program video component, and motion estimating vectors of each of the replacement pictures being set to a zero value.

[033] In either of the above cases, said replacement pictures are frame pictures comprising a TOP frame and a BOTTOM frame which as a result are similar to digital television pictures and their predictions are field-based predictions. Therefore the TOP and BOTTOM frames of the first predictive replacement picture P refer to the sole BOTTOM frame of the last predictive picture P or I of the first-program video component, and the TOP and BOTTOM frames of the predicted P or bidirectional B pictures which follow refer to the BOTTOM frame of the first predictive replacement picture P.

[034] In another implementing mode of the method of the present invention, the replacement pictures constitute a sequence of pictures which, in the order of transmission, consists of a first picture which is an Intra picture, the other pictures being alternating bidirectional and predictive pictures, the first predictive replacement picture P referring to the Intra picture, then each following predictive replacement picture P referring to the predictive picture P which precedes it, and each bidirectional replacement picture B only referring to the predictive picture P or Intra picture which precedes it, the number of bidirectional pictures B between two predictive pictures P being equal to that encountered in the first-program video component, and the motion estimating vectors of each of the replacement pictures being set to a zero value except for the Intra picture which is without a motion estimating vector. Said replacement pictures are frame pictures which may comprise a TOP frame and a BOTTOM frame which as a result are pictures similar to those of digital television and the predictions of the bidirectional pictures B and the predictive pictures P are field-based predictions. The TOP and the BOTTOM frames of the replacement pictures B or P which follow the picture I then refer to the BOTTOM frame of the replacement picture I or P which precedes it.

[035] The method of the present invention can be implemented in a transmission system wherein said pictures each constituting video components of the first and second programs are transported by transport packet streams, each transport packet TP being fitted with a PUSI (payload unit start indicator) indicator which, when set at 1, denotes that said packet contains the beginning of a PES (packetized elementary

stream) packet, the PES packets being aligned with the beginning of payload of the transport packets TP, each PES packet containing a single picture, said transport system being such that certain transport packets are made to carry transport data such as a random access indicator (RAI) which, when set at 1, denotes that the next transport packet moving this component shall contain the first data of a video sequence. In this case said system consists in the following:

-- determining the first transport packet TP of the first-program video component which is present after the switch command and which comprises a random access indicator RAI set at 1 in order to determine the time of switching at the second program,

-- switching onto said second-program video component and replacing the transport packets TP of this video component with stuffing transport packets until the appearance of the following transport packet TP of which the PUSI indicator is set at 1,

-- in this transport packet TP, of which the PUSI indicator is set at 1, and provided the RAI indicator is NOT set, replacing the PES packet header situated at the beginning of the payload by a reconstructed PES packet header,

-- starting with this transport packet and after the PES packet header, replacing the payload data of each transport

packet of this component with the replacement picture data and when all data of the replacement picture have been inserted into the video component transport packet payloads, replacing the payload data of following transport packets TP of the component with video stuffing such as '00 octets until the appearance of the next transport packet of this second-program video component of which the PUSI indicator is set at 1, this transport packet TP excluded,

-- then restarting the preceding stage from this transport packet TP with the PUSI indicator set at 1 until the appearance of the next transport packet of the second-program video component of which the random access indicator RAI is set at 1, this transport packet excluded,

-- setting the discontinuity indicator DI at 1 on this packet with the random access indicator RAI which corresponds to the end of replacement and to the actual beginning of the second program video.

[036] Advantageously, if the transport packets TP are scrambled, said method consists in denoting them in clear by setting the transport scrambling control TSC field at the binary value 00.

[037] Said method can be implemented in a transmission system wherein said pictures each constituting video components of the first and second programs are transported by transport packet streams, each

transport packet TP comprising a PUSI indicator which, when set at 1, denotes that said packet contains the beginning of a PES packet, these PES packets being aligned with the beginning of the payload of the transport packets TP, each PES packet containing a single picture, said transmission system consisting in the following: certain transport packets are intended to carry transport data such as a random access indicator RAI which, when set at 1, denotes that the next transport packet moving this component contains the first data of a video sequence, said method then consisting in:

-- determining the first transport packet of the first-program video component which is present after the switch command and which comprises a random access indicator RAI set at 1 to determine the switching time onto the second program,

-- switching onto said second-program video component and replacing the transport packets TP of this video component with stuffing transport packets until the appearance of the following transport packet TP of which the PUSI indicator is set at 1,

-- if the RAI indicator is set and starting with this transport packet and after the PES header, replacing the payload data of each transport packet of this component with replacement image data and when all replacement image data have been inserted in the payload of the video component transport packets TP, replacing the payload data of the

following transport packets TP of the component with video stuffing such as '00 octets until the appearance of the next transport packet of this second-program video component of which the PUSI indicator is set at 1, this TP transport packet excluded,

-- then beginning again with the previous stage based on this transport packet TP with the PUSI indicator set at 1 until the appearance of the next transport packet TP of the second-program video component of which the random access indicator RAI is set at 1, this transport packet excluded,

-- setting the discontinuity indicator DI at 1 on this packet with random access indicator RAI which corresponds to the end of replacement and to the actual beginning of the second program video.

[038] In case neither of the video components is fitted with a random access indicator RAI set in the transport stream, said method of the invention moreover consists in:

-- determining the video component transport packet TP of the stream(s) without RAI indicator of which the PUSI indicator is set at 1 and of which the payload data begin with a video sequence header,

-- carrying out a search for the sequence header after the switch command,

-- setting the discontinuity index in the determined transport packet TP if latter comprises an adaptation field AF with a program clock reference PCR in the case of the component bearing the program clock,

-- or if the determined transport packet TP does not comprise an adaptation field AF or if the component bearing the program clock is involved and the adaptation field AF does not comprise a PCR clock reference, replacing the determined transport packet TP with a specific transport packet TP called the inserted transport packet and shifting the replaced transport packet TP as well as the following transport packets of this video component in the transport stream until one of them can be inserted into a stuffing transport packet TP.

[039]        Advantageously the inserted transport packet TP exhibits the following advantages:

-- the PUSI indicator is set at 0,

-- the status of the continuity counter COP is set at that of the continuity counter of the initial transport packet, less 1,

-- the control field AFC of the adaptation field AF is set at the binary value 00 denoting that an adaptation field AF, but not a payload, is present in this transport packet TP,

-- the discontinuity indicator DI situated in the adaptation field AF is set at 1,

-- if the video component carries the program clock reference PCR, set a PCR clock calculated on the basis of the preceding PCR clocks of the same component in the adaptation field AF.

[040] In case a presentation time stamp PTS is present in the header of the PES packet containing the sequence header, the method of the invention pre-processes the setting of the RAI indicator, said transport packet TP which was inserted to set the random access indicator then exhibiting the following features:

-- the PUSI indicator is set at 0,

-- the status of the discontinuity counter COMP is set to that of the discontinuity counter of the initial transport packet TP less 1,

-- the control field AFC of the adaptation field AF is set to the binary value 10 denoting thereby that an adaptation field is present in this transport packet TP, but not a payload,

00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000



-- the RAI indicator situated in the adaptation field AF is set at 1,

-- the discontinuity indicator DI situated in the adaptation field is set,

-- if the video component carries the program clock, a program clock reference PCR calculated on the basis of the preceding clock reference(s) PCR of the same component is set in the adaptation field AF.

[041] In case the presentation stamp is absent from the header of the PES packet containing the sequence header and if the initial transport packet is modified in a manner that its PUSI indicator is set at 0 and payload data are suppressed in the PES packet header, then said transport packet TP inserted to set the RAI indicator will exhibit the following characteristics:

-- the PUSI indicator is set at 1,

-- the status of the continuity counter COMP is set at that of the continuity counter of the initial transport packet TP, less 1,

-- the control field AFC of the adaptation field AF is set at the binary value 11, denoting that an adaptation field and a payload are present in this transport packet,

-- the adaptation field AF comprises an RAI indicator set at 1,

-- the discontinuity indicator is set at 1 on this packet with RAI indicator,

-- a program clock reference PCR calculated on the basis of the preceding clock reference(s) PCR of the same component is set in the adaptation field AF if the video component bears the program clock,

-- a presentation stamp PTS is calculated and positioned in this packet's payload,

-- the PES packet header in the replaced transport packet TP is moved into the payload of this inserted transport packet TP and in case the presentation stamp PTS is absent from the PES packet header, said stamp PTS is calculated and positioned in the header data of this PES packet.

[042] The above cited features of the invention as well as further ones are elucidated below in the following description of several implementing modes of the invention, said description relating to the attached drawings also.

[043] Fig. 1 is a view illustrating a switching method of a first implementing mode of the invention,

[044] Fig. 2 illustrates a switching procedure of a second implementing mode of the invention,

[045] Fig. 3 illustrates a switching procedure of a third implementing mode of the invention,

[046] Fig. 4 illustrates a switching procedure of a fourth implementing mode of the invention,

[047] Fig. 5 illustrates a switching procedure of the first implementing mode of Fig. 1 wherein the pictures comprise a top and a bottom frame,

[048] Fig. 6 illustrates a switching procedure of the second implementing mode of Fig. 3 wherein the pictures comprise a top and a bottom frame,

[049] Fig. 7 illustrates a switching procedure of the implementing mode of Fig. 3 wherein the pictures comprise a top and a bottom frame,

[050] Fig. 8 illustrates a switching procedure of the implementing mode of Fig. 4 wherein the pictures comprise a top and a bottom frame,

[051] Fig. 9 illustrates a switching procedure of the invention in the transport mode, and

[052] Figs. 10a - 10c illustrate the insertions of a transport packet fitted with an RAI indicator set at 1.

[053] In the illustrative implementation now being described, the structure of the groups of pictures GOP of the two video streams under consideration and generally characterized by a gap between two P pictures (the M parameter in the MPEG-2 standard) and by a gap between two I pictures (called the N parameter in the MPEG-2 standard) is such that the parameter when being 2 denotes a single bidirectional picture B being placed between two consecutive predictive pictures P. As regards the N parameter, its value is arbitrary, the number of pictures in a group of pictures GOP being immaterial in the invention.

[054] It must be borne in mind that each program may comprise several video components, for instance components which correspond to different fields of view of the program (several cameras for instance). The invention applies to each component, but for the sake of simplicity, herebelow, the description shall relate to a single video component for each program.

[055] Fig. 1 shows an elementary video stream F1 of a first program and an elementary video stream F2 of a second program. Each stream F1, F2 consists of a sequence of groups of pictures GOP comprising Intra I pictures, bidirectional B pictures and predictive P pictures. These pictures are shown in the order of their transmissions.

[056] Fig. 1 shows that the PES packets and the transport packets are absent from the implementation.

[057] The switch command is shown by the arrow A and occurs during the group of pictures GOP1. This group of pictures GOP1 is the last transmitted group of pictures of the first-program video component.

[058] In one illustrative mode of implementation of the invention, the group of pictures GOP1 must end before switching the video component of the stream F1 onto the video component of the stream F2. This switching is indicated by an arrow B in Fig. 1. In this Figure, the group of pictures GOP2 is the first group of pictures of the second-program video component that shall be transmitted after switching.

[059] According to the invention, switching onto the second-program video component takes place at the above defined time (arrow B) and then each picture of this component is replaced by a picture of which the coding is implemented independently of the picture data of the replaced picture and of the contents of its related pictures until the beginning of the next group of pictures of said second program component. These replacements take place for each picture of the incomplete group GOPs. They are denoted by the vertical arrows between the replacement pictures and the replaced pictures.

[060] In Fig. 1, the switching onto the second-program video component takes place after the last picture of the group of pictures of the first component video component which was transmitted after the

switch command. The data present in the second-program video component between the end of the group of pictures GOP1 and the beginning of the first picture are replaced by stuffing data (denoted b in Fig. 1). Depending on the case, these stuffing data may be those in the video syntax, those in the PES packet syntax or those in the transport syntax.

[061] Illustratively and according to an implementation mode of the MPEG-2 transport standard, those will be stuffing transport packets. The replacement pictures of the incomplete group of pictures GOP of the second program are denoted group of pictures GOPs. As shown by Fig. 1, the group of pictures GOPs consists of a sequence of bidirectional B pictures all referring to the last P (or I) type picture of the last group of pictures GOP1 of the first program (in Fig. 1, arrows represent this reference). These are forward references in the order of presentation. Moreover, the motion estimating vectors of each of the replacement pictures B are set to a zero value, making it possible to freeze the last P or I picture of the first program.

[062] In Fig. 2, the replacement group GOPs consists of a picture P followed by a sequence of B pictures, where these bidirectional B pictures refer to said picture P. As regards the predictive P picture of the group GOPs, it refers to last P (or I) picture of the last group of pictures GOP1 of the first-program video component (forward reference in the order of presentation). Also, the motion estimating vectors of each of the predictive P pictures or bidirectional replacement pictures B are set to a zero value, making it possible to freeze the last P or I picture of the first program.

[063] In this second implementing mode, the presence of the replacement picture P allows avoiding an unpleasant effect otherwise taking place at the end of replacement where interleaved pictures are concerned.

[064] In Fig. 3 the replacement group GOPs consists of a sequence of alternating P or B pictures. The first replacement picture P relates to the last P or I picture of the last group of pictures GOP1 of the first-program video component. Each ensuing replacement picture P refers to the P picture which precedes it. Each replacement picture B refers to the P picture immediately preceding it. Therefore each P or B picture refers forward in the order of presentation. Also the motion estimating vectors of each of the replacement pictures P or B are set to a zero value, making it possible to freeze the last P or I picture of the first program.

[065] In Fig. 4, the replaced group GOPs consists of a sequence of pictures of which the first is an I picture, the second a B picture, the third a P picture, the fourth a B picture, etc. The first replacement P picture refers to the replacement picture I. Each following replacement picture P refers to the replacement picture P which precedes it. Each replacement picture B refers to the replacement picture P immediately preceding it. Each P or B picture therefore constitutes a forward reference in the order of presentation. Furthermore the motion estimating vectors of each replacement picture P or B are set to a zero value, making it possible to freeze the replacement I picture.

[066] This fourth implementing mode allows inserting advertizing spots framed by fixed pictures, for instance colored pictures or logos.

[067] The present invention also applies to systems supporting interleaved pictures. This is the case for the systems under the MPEG-2 standard. In such systems, each picture comprises two frames, a TOP frame and a BOTTOM frame. The prediction of the macroblocks of these two frames may be frame-based or field-based. For perfect control and in order to avert "going backward", the prediction must be field based for each frame.

[068] In the implementing mode shown in Fig. 5 and corresponding to the implementation of Fig. 1, the BOTTOM and TOP frames of each replacement bidirectional B picture refer to a single frame of the predictive P picture of the first program group of pictures GOP1. In Fig. 1, this frame is the BOTTOM frame. However it may also be the TOP frame.

[069] Accordingly the frame of the P picture of the group of pictures GOP1 of the first program is maintained by the two BOTTOM and TOP frames of the replacement B pictures of the group of pictures GOPs. This implementation entails a drawback in the case of interleaved pictures: the P picture is displayed after the replacement pictures B as seen in the order of presentation. As a result, the impression of an advance is given at the end of the freeze because of the display of the BOTTOM frame of the P picture of the first program group of pictures GOP1. If the video is sluggish, this phenomenon will not be bothersome.



[070] In the illustrative implementation of Fig. 6, corresponding to the implementation of Fig. 2, the two TOP and BOTTOM frames of the replacement picture P of the replacement group of pictures GOPs refer to a single frame of the picture P of the group of pictures GOP1 of the first program. Advantageously this frame shall be the BOTTOM frame. As regards the following picture B, its BOTTOM and TOP frames each refer to the BOTTOM frame of the P picture preceding it. The BOTTOM and TOP frames of each replacement picture B of the group of pictures GOPs maintain the BOTTOM frame of the substitution picture P.

[071] This implementing mode allows attaining a perfect freeze from which any visual defect is excluded using interleaved pictures. However one drawback is the difficulty in updating the time reference of the replacement picture P.

[072] In the implementing mode of Fig. 7 corresponding to the implementation of Fig. 3, the two TOP and BOTTOM frames of the first replacement picture P of the group of pictures GOPs refer to a single frame of the predictive picture P of the first program group of pictures GOP1. Advantageously this frame shall be the BOTTOM frame. The BOTTOM and TOP frames of each P picture and of each B picture of the replacement group of pictures GOPs refer to the single BOTTOM frame of the P picture which precedes it.

[073] This implementing mode allows perfect freezing without any visual defects using interleaved pictures and updating the time reference entails no problems.

[074] In the implementing mode of Fig. 8 corresponding to the implementation of Fig. 4, the TOP and BOTTOM frames of each P picture and of each B picture of the group of pictures GOPs refer to the single BOTTOM frame of the I or P picture which directly precedes it as seen in the order of transmission.

[075] This mode of implementation allows perfect freezing without any visual defects with interleaved pictures and updating the time reference will not entail any problems.

[076] The above cited references are carried out by setting the particular indicators in the macroblocks of the particular replacement pictures. All replacement picture macroblocks are coded to avert default-referencing the frames on the frame of the same parity (TOP on TOP and BOTTOM on BOTTOM) and dissociating each one's prediction.

[077] Furthermore the picture patterns of the replacement group of pictures GOPs all must exhibit the same characteristics (resolution, or horizontal a vertical sizes in particular) as the pictures they replace. A number of means are available to retrieve the size information: it may be retrieved from the target background grid descriptor (if any) in the program map table, and it may be retrieved directly from the data of the video elementary stream etc.

[078] Also, the time reference (order of the pictures to be displayed) of each replacement picture must be updated.

[079] Lastly and to follow the standard, the VbV delay which is the least wait before it is possible to code a picture once the first picture octet has reached the decoder's buffer memory, is defined as follows:

-- if said delay is situated in the other pictures of the group of pictures GOP2, it also must be situated the pictures of the replacement group: it may be retrieved from the replaced picture,

-- if the delay is at 'FFFF' in the other pictures of the group of pictures GOP2, it must also be set at 'FFFF' in the pictures of the replacement group.

[080] As cited above, according to the MPEG-2 standard, the elementary stream packets PES comprise a header h and a payload with the data of a portion of one picture, of one picture or of several pictures (in general one picture) and are cut into transport packets TP. In case the payload of a PES packet contains the data of a single picture, the PES packets are aligned and the corresponding data alignment indicator is set at 1.

[081] Again according to the MPEG-2 standard, the transport packets of which the payload begins with the header h of a PES packet contain in their actual header H a specialized PUSI (payload unit start) indicator: this PUSI indicator is set at 1. Therefore transport packets of which the PUSI indicator is set at 1 contain the first data relating

to a particular picture (this also is the case for the TP2, TP3 and TP5 packets of Fig. 9).

[082] Other transport packets intended to carry transport information contain an adaptation field AF. In this adaptation field AF, a random access indicator RAI indicates, when set at 1 (for example in the transport packet TP1 or the packet TP4 of Fig. 9), that the next transport packet of which the PUSI indicator is set at 1 (resp. here the transport packet TP2 and the packet TP5), contains not only a beginning of a PES packet but also a beginning of a video sequence in the PES packet.

[083] Be it noted that the transport packet TP of which the PUSI indicator is set at 1 may be the one of which the random access indicator RAI also is set at 1.

[084] The adaptation field furthermore contains a discontinuity indicator DI which, when set at 1, indicates discontinuity starting with the transport packet TP, namely discontinuity of the continuity counter or discontinuity of the PCR clock reference if the component carries the PCR clock references.

[085] Therefore two streams of transport packets are available in the invention (Fig. 9). The first transport stream Ft1 relates to the transport packets of the first program and the second transport stream Ft2 relates to the transport packets of the second program.

[087] Switching one video program onto another in the transport mode mainly consists in replacing the transport packets TP of the first-program video component with the transport packets TP of the second-program video component with the transport packets TP of the second-program video component, if necessary accompanied by re-stamping.

[088] Following the switch command (denoted by the arrow A in Fig. 9), the end of the sequence (of the group of pictures GOP1) in the first program must be awaited. The next transport packet in the transport stream Ft1 of the first program of which the random access indicator RAI is set at 1 (in this instance the transport packet TP1), will determine the time of switching onto the second program.

[089] From that time on, the transport packets TP of the first-program video component are replaced with stuffing transport packets TP (denoted "b" in Fig. 9) until the appearance of the PUSI indicator of a transport packet TP of the transport stream Ft2 of the second program be set at 1. When such a packet denoting an image beginning in the stream Ft2 presents itself (in this example the TP3 packet), replacement may begin. This replacement will continue until the appearance of a packet, in this case TP4, shall appear in the transport stream Ft2, the header of said packet containing an RAI indicator be set at 1 denoting a beginning of sequence (in this case a group of pictures GOP2).

-- the PES packet header situated at the beginning of the payload is replaced in the transport packet TP of which the PUSI indicator is set at 1 with a header of a reconstructed PES packet; in an advantageous embodiment mode, the various fields of this header assume the following values: start code = 0x000001, flux stream indicator = that of the first program, PES packet length = 0x0000, 2 flag octets = 0x8500, header data length = 0x00, PES packets in clear, no PTS/DTS stamps nor any other data of PES packet header,

-- beginning with this transport packet (after the PES packet header), the data of the payload of each transport packet of this component shall be replaced by the data of replacement picture (Intra picture I, bidirectional picture B or predictive picture P depending on the replacement mode selected from the above described mode and on the replaced picture). If the transport packets TP are scrambled, they shall be denoted in clear by setting the control field of the transport scrambling control TSC at the binary value 00; note should be taken that the access control messages ECM (rights control messages) containing the cryptograms of the control words continue being emitted,

-- when all replacement picture data have been inserted into the payloads of the video component transport packet TP, replacement continues by replacing the payload data with video stuffing (namely '00 octets) until the appearance of the next transport packet of this second-program video component of which the PUSI indicator is set at 1 (this transport packet TP excluded),

-- then restarting the three preceding stages from this new transport packet TP with the PUSI indicator set at 1 until the appearance of the next transport packet TP of the second-program video component of which the RAI indicator is set at 1 (excluded),

-- setting the discontinuity indicator DI at 1 on this packet fitted with the RAI indicator, corresponding to the end of replacement and to the effective beginning of the second program video.

[091] In case the RAI indicators are absent from one or both transport streams, a method of the invention allows finding the sequence headers in the payloads of the transport packets TP at the time of switching. This method consists in determining during a first time interval the transport packet TP of the video component of the stream(s) lacking an RAI indicator of which PUSI indicator is set at 1 and of which the payload data begin with a video sequence header.

[096]       The inserted transport packet TPins exhibits the following features (lower line of Fig. 10a):



-- the PUSI indicator is set at 0: this indicates that this transport packet TP lacks the beginning of a PES packet,

-- the status of the continuity counter is set at that of the initial transport packet's (TP's) continuity counter , less 1 (here:  $5 - 1 = 4$ )

-- the control field AFC of the adaptation field AF is set at the binary value 10 denoting the presence of an adaptation field in this transport packet TP, but no payload,

-- the discontinuity indicator DI situated in the adaptation field AF is set at 1.

-- if the video component carries the program clock, a program clock reference PCR calculated after the PCR clock references preceding the same component is moved into the adaptation field AF.

[097] The transport packet TP replaced by TP1 which is neither suppressed nor modified. It is phase-shifted, and so are the following transport packets TP of this video component in the transport stream until one of them can be inserted into a stuffing transport packet TP.

[098] In case the RAI indicators are absent from one or both transport streams but are used in implementing switching, the invention

also provides pre-processing to make it possible to insert them several seconds before re-connection.

[099] As stated above in relation to the MPEG-2 system standard, the RAI indicator is situated the adaptation field AF. Set at 1, it denotes that the next transport packet TP of this component which contains a PES packet beginning (and hence a PUSI indicator set at 1) will comprise a sequence header in its payload. Also, all synchronization data must be present in the transport packet TP of which the RAI indicator is set at 1, in particular a PCR clock reference if the component carries the program clock and the presentation time stamp PTS in the PES packet header.

[100] In case a presentation stamp PTS is present in the header of the PES packet containing the sequence header, the transport packet TP inserted to set the RAI indicator exhibits the same characteristics as before, but the RAI indicator situated in the adaptation field AF is set at 1. The replaced transport packet TP is unmodified but shifted, as are the following transport packets TP of this video component, in the transport stream until one of them can be inserted into a stuffing transport packet TP.

[101] This case is illustrated in Fig. 10b.

[102] Fig. 10c shows the case when the presentation stamp PTS is absent from the header of the PES packet which contains the sequence

2

- ```
-- the PUSI indicator is set at 1: this denotes that the PES
packet header is located in the payload,

-- the status of the continuity counter COMP is set at that
of the continuity counter of the initial transport packet TP
less 1 ( $5-1 = 4$ ,

-- the field control AFC of the adaptation field AF is set
at the binary value 11, denoting that an adaptation field and
a payload are present in this packet,

-- the adaptation field AF comprises an RAI indicator set at
1,

-- the discontinuity indicator DI is set at 1,

-- if the video component carries the program clock, a
program clock reference PCR is situated in the adaptation
field and is calculated based on the preceding PCR
reference(s) of the same component,

-- a presentation stamp PTS is calculated and situated in
this packet's payload,
```

-- the PES packet header which was situated in the replaced transport packet TP is displaced in the payload of this inserted transport packet TP and if the presentation stamp PTS is absent from the PES packet header, this PTS stamp shall be calculated and situated into the header data of this PES packet.

[103] The replaced transport packet TP therefore is modified in a manner that its PUSI indicator shall be set at 1 and in that it lacks the PTS packet header. This transport packet TP is shifted in the transport stream, and so are the following transport packets TP of this video component, until one of them can be inserted into a stuffing transport packet.

[104] It should be borne in mind that this last solution can hardly be considered for the case of the second program being scrambled unless rigorous operating rules be adopted: in case the second program were to share the entitlement control messages ECM linked to scrambling these components with other programs, said ECM messages would require a particular processing procedure (for instance being recreated) in order not to delay the other programs.

## CLAIMS

1. A method for switching the video component(s) of a first digital audio-visual program onto the video component(s) of a second digital audio-visual program, each video component being constituted, as seen in the order of presentation, by an ordered sequence of pictures which are either Intra pictures (denoted by I) or predictive pictures (denoted by P) or bidirectional pictures (denoted by B), each Intra picture referring to no other picture, each predictive picture referring to the Intra picture or to the predictive picture preceding it, each bidirectional picture being able to refer to two non-bidirectional pictures Intra or P, either to the Intra picture or to the predictive picture preceding it or to the Intra picture or the P picture following it, or to a combination of the two preceding or following Intra or predictive pictures,

characterized in that

said method consists in switching at a switching time following the end of a picture of the first program after the switch command onto the picture of the video component of the second program which is present at said time and in replacing, as seen in the order of transmission, each picture other than Intra of said second program component, where said latter picture is situated between the switching time and the beginning of the next Intra picture of said second program component, with a picture of which the coding is carried out independently of the picture data of the replaced picture and of the contents of the pictures to which the replacement picture refers.

2. Method as claimed in claim 1, characterized in that the information present in the second-program video component between the time at which the end of a picture of the first-program video component has been encountered after having received the switch command and the beginning of the first picture of the second program is replaced with stuffing data.

3. Method as claimed in either of claims 1 and 2, characterized in that the time references of each replacement picture are updated.

4. Method as claimed in one of the above claims, characterized in that the information relating to the minimum delay Vbv before it is possible to decode a picture is retrieved from the replaced picture and moved into each corresponding substitution picture unless it be equal to 'FFFF' in the other pictures of said second program component, in which latter case it assumes the value 'FFFF'.

5. Method as claimed in one of the above claims, characterized in that the replacement pictures constitute a sequence of bidirectional B pictures all referring to the last predictive P picture of the first-program video component, the motion estimating vectors of each of the bidirectional replacement pictures being set to a zero value.

6. Method as claimed in claim 5, characterized in that said replacement B pictures are interleaved pictures comprising a BOTTOM frame and a TOP frame which thereby are similar to digital television pictures and their predictions are field-based predictions, the TOP

frames and the BOTTOM frames of said B replacement pictures referring to the single BOTTOM frame of the last predictive picture P of the first-program video component.

7. Method as claimed in claim 1 through 4, characterized in that the replacement pictures constitute a sequence of picture which as seen in the direction of transmission consists of a predictive picture followed by one or more bidirectional pictures, the predictive replacement picture P referring to the last predictive picture P of the first-program video component and each of the bidirectional pictures B referring to said replacement picture P, the motion estimating vectors of each of the replacement pictures being set to a zero value.

8. Method as claimed in claim 1 through 4, characterized in that the replacement pictures constitute a sequence of pictures which consists, as seen in the direction of transmission, of alternating predictive and bidirectional pictures, the first predictive replacement picture P referring to the last predictive picture P or Intra picture I of the first-program video component, then each following predictive replacement picture P referring to the predictive picture P which precedes it, and each bidirectional replacement picture B referring only to the predictive picture P which precedes it, the number of bidirectional pictures B between two predictive pictures P being equal to that encountered in the first-program video component, and the motion estimating vectors of each replacement picture being set to a zero value.

9. Method as claimed in either of claims 7 and 8, characterized in that said replacement pictures are frame pictures comprising a TOP frame and a BOTTOM frame which thereby are similar to digital television picture and their predictions are field-based predictions, the TOP and BOTTOM frames of the first predictive replacement picture P referring to the single BOTTOM frame of the last predictive picture P or I of the first-program video component and the TOP and BOTTOM frames of the following bidirectional B or predictive P pictures referring to the BOTTOM frame of the first predictive replacement picture P.

10. Method as claimed in claim 1 through 4, characterized in that the replacement pictures constitute a sequence of pictures which consists as seen in the order of transmission of a first picture which is an Intra picture, the other pictures being an alternation of bidirectional and predictive pictures, the first predictive replacement picture P referring to the Intra picture, then each following predictive replacement picture P referring to the predictive picture P which precedes it, and each bidirectional replacement picture B only referring to the predictive picture P or the Intra picture I which precedes it, the number of bidirectional pictures B between two predictive pictures P being equal to that encountered in the first-program video component and the motion estimating vectors of each replacement picture being set to a zero value except for the Intra picture which lacks motion estimating vectors.

11. Method as claimed in claim 10, characterized in that said replacement pictures are frame pictures comprising a TOP frame and a



BOTTOM frame which thereby are pictures similar to those of digital television, and the predictions of the bidirectional pictures B and the predictive pictures P being field-based predictions, the TOP and the BOTTOM frames of the P or B replacement pictures which follow the picture I referring to the BOTTOM frame of the I or P replacement picture which precedes it.

12. Method as claimed in one of claims 5 through 11, which is implemented in a transmission system wherein said pictures each constituting video components of the first and second programs are transported by transport packet streams, each transport packet TP being fitted with a payload unit start PUSI indicator which, when set at 1, indicates that said packet contains the beginning of a packetized elementary stream PES packet, the PES packets being aligned with the beginning the payloads of the transport packets TP, each PES packet containing only one picture, wherein said transmission system certain transport packets are intended to carry transport information such as a random access indicator RAI which, when set at 1, denotes that the next transport packet moving this component contains the first data of a video sequence,

characterized in that  
said method consists

-- determining the first transport packet TP of the first-program video component after the switch command , said packet comprising a random access indicator RAI set at 1 in

order to determine the time of switching onto the second program,

5       -- switching onto said second-program video component and replacing the transport packets TP of this video component with stuffing transport packets until the appearance of the following transport packet TP of which the PUSI indicator is set at 1,

10       -- within this transport packet TP of which the PUSI indicator is set at 1 and if the RAI indicator is not set, replacing the PES packet header situated at the beginning of the payload with a reconstructed PES packet header,

15       -- starting with this transport packet and after the PES packet header, replacing the payload data of each transport packet of this component with the replacement picture data and when all replacement picture data have been inserted into the payload of the video component transport packets TP, replacing the payload data of the following transport packets  
20       TP of the component with video stuffing such as '00 octets until the appearance of the next transport packet of this second-program video component of which the PUSI indicator is set at 1, this transport packet TP excluded,

25       -- then restarting the preceding stage from this transport packet TP with PUSI indicator set at 1 until the appearance

of the next transport packet TP of the second-program video component of which the random access indicator RAI is set at 1, this transport packet excluded,

5       -- setting the discontinuity indicator DI at 1 on this packet with random access indicator RAI which corresponds to the end of replacement and to the effective beginning of the second program video.

10       13. Method as claimed in claim 12, characterized in that when the transport packets TP are scrambled, this method consists in denoting them in clear while setting the control field of transport scrambling control TSC at the binary value 00.

15       14. Method as claimed in one of claims 5 through 11 and being implemented in a transmission system wherein said pictures each constituting the video components of the first and second programs are moved by transport packet streams, each transport packet TP comprising a payload unit start indicator PUSI which when set at 1 denotes that  
20       said packet contains the beginning of packetized elementary stream PES packet, the PES packets being aligned with the beginning of the transport packet TP payloads, each PES packet containing only one picture, said transmission system being such that certain transport  
25       packets are intended to carry transport information such as a random access indicator RAI which, when set at 1, indicates that the next transport packet moving this component contains the first data of a video sequence,

characterized in that

said method consists in:

5       -- determining the first transport packet TP of the first-  
program video component present after the switch command and  
comprising a random access indicator RAI set at 1 in order  
to determine the time of switching onto the second program,

10       -- switching onto said second-program video component and  
replacing the transport packets TP of said video components  
with stuffing transport packets until the appearance of the  
following transport packet TP of which the PUSI indicator is  
set at 1,

15       -- if the RAI indicator is set based on this transport packet  
and after the PES packet header, then replacing the payload  
data of each transport packet of this component with the  
replacement picture data, and when all the replacement  
picture data have been inserted in the payload of the video  
20       component transport packets TP, substituting the payload data  
of the following transport packets TP of the component with  
video stuffing such as '00 octets until the appearance of the  
next transport packet of this second-program video component  
of which the PUSI indicator is set at 1, this transport  
25       packet TP excluded,

-- then restarting the preceding stage on the basis of this transport packet TP with the PUSI indicator set at 1 until the appearance of the next transport packet TP of the second-program video component of which the random access indicator RAI is set at 1, this transport packet excluded,

-- setting the discontinuity indicator DI at 1 on this packet with the random access indicator RAI, which corresponds to the end of replacement and to the effective beginning of the second program video.

15. Method as claimed in one of claims 12, 13 or 14, for the case of one or both video components being devoid of a random access indicator RAI set in the transport stream, characterized by consisting in:

-- determining the transport packet TP of the video component of the stream(s) without RAI indicator of which the PUSI indicator is set at 1 and of which the payload data begin with a video sequence header,

-- searching for the sequence header following the switch command,

-- setting the discontinuity index in the determined transport packet TP if latter comprises an adaptation field

AF with a program clock reference PCR when the component carries the program clock,

-- or if the determined transport packet TP does not comprise an adaptation field AF or if the program clock carrying component is involved and the adaptation field AF lacks a clock reference PCR, replacing the determined transport packet TP with a specific transport packet TP called the inserted transport packet and shifting the replaced transport packet TP as well as the following transport packets TP of this video component in the transport stream until one of them can be inserted into a stuffing transport packet TP.

16. Method as claimed in claim 15, characterized in that the inserted transport packet exhibits the following characteristics:

-- the PUSI indicator is set at 0,

-- the status of the continuity counter COMP is set at that of the continuity counter of the initial transport packet TP less 1,

-- the control field AFC of the adaptation field AF is set at the binary value 10, denoting the presence of an adaptation field AF in this transport packet TP, but no payload,

-- the discontinuity indicator DI situated in the adaptation field AF is set at 1,

-- if the video component carries the program clock, a program clock reference PCR calculated on the basis of the preceding clock reference(s) PCR of the same component is set into the adaptation field.

17. Method as claimed in claim 15, for the case of a presentation stamp PTS being present in the header of the PES packet containing the sequence header, characterized in that it consists in pre-processing the setting of the random access indicator RAI , said transport packet TP inserted to set the random access indicator RAI then exhibiting the following characteristics:

-- the PUSI indicator is set at 0,

-- the status of the continuity counter COMP is set at that of the continuity counter of the initial transport packet TP, less 1,

-- the control field AFC of the adaptation field AF is set at the binary value 10 denoting that an adaptation field AF is present in this transport packet TP but no payload,

-- the RAI indicator situated in the adaptation field AF is set at 1,

-- the discontinuity indicator DI situated in the adaptation field is set,

-- if the video component carries the program clock, a program clock reference PCR calculated on the basis of the preceding clock reference(s) PCR of the same component is moved into the adaptation field AF.

18. Method as claimed in claim 15, for the case of the presentation stamp being absent from the header of the PES packet containing the sequence header, characterized in that it consists in pre-processing the setting of the RAI indicator, in that the initial transport packet TP is modified in such a way that its PUSI indicator is set at 0 and the useful data are eliminated from the PES packet header, said transport packet TP inserted to set the RAI indicator then exhibiting the following features:

-- the PUSI indicator is set at 1,

-- the status of the continuity counter COMP is set at that of the continuity counter of the transport packet TP less 1,

-- the control field AFC of the adaptation field AF is set at the binary value 11 to denote that an adaptation field AF and a payload are present in this transport packet,



-- the adaptation field AF comprises an RAI indicator set at 1,

-- the discontinuity is set at 1 on this packet with RAI indicator,

-- a program clock reference PCR calculated on the basis of the preceding clock reference(s) is set in the adaptation field AF if the video component carries the program clock,

-- a presentation stamp PTS is calculated and moved into the payload of this packet,


-- the PES packet header which was in the replaced transport packet TP is shifted into the payload of this inserted transport packet TP and in case of the absence of the presentation stamp PTS from the PES packet header, this PTS stamp shall be calculated and set in the header data of this PES packet.

## ABSTRACT



The present invention relates to a method for switching the video component(s) of a digital audio-visual first program onto the video components of a second digital, audio-visual program.


In the invention, said method is characterized in that it consists in switching onto the video component of the second program, subsequent to the switch command and to the end of a picture of the first program, and in replacing, as seen in the order of transmission, each non Intra picture of said component of said second program, with a picture of which the coding is carried out independently of the picture data of the replaced picture and of the contents of the pictures to which it refers until the beginning of the next Intra picture of said component of said second program.

09/807620



2/9

FIG. 2FIG. 3






FIG. 5




FIG. 6




FIG. 7






FIG.8







FIG. 9



## DECLARATION FOR PATENT APPLICATION AND APPOINTMENT OF ATTORNEY

As a below-named inventor, I hereby declare that my residence, post office address and citizenship are as stated below next to my name; I believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention (Design, if applicable) entitled: A METHOD SWITCHING THE VIDEO COMPONENT(S) OF A FIRST DIGITAL, AUDIO-VISUAL PROGRAM ONTO THE VIDEO COMPONENTS OF A SECOND DIGITAL, VIDEO-AUDIO PROGRAM TO COMPENSATE THEIR PHASE SHIFT

the specification of which (check one):

- ☐ is attached hereto.  
☒ was filed on April 16, 2001 as Application Serial No. 09/807,620.  
☒ was filed on October 14, 1999 as International Application (PCT) No. PCT/FR99/02469, and was amended on \_\_\_\_\_ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment(s) referred to above. I acknowledge the duty to disclose information which is material to the examination of this application in accordance with *Title 37, Code of Federal Regulations, § 1.56*. I hereby claim foreign priority benefits under *Title 35, United States Code § 119* of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which the priority is claimed.

### PRIOR FOREIGN APPLICATION(S)

| NUMBER   | COUNTRY | DAY/MONTH/YEAR FILED | PRIORITY CLAIMED                                                    |
|----------|---------|----------------------|---------------------------------------------------------------------|
| 98/12973 | FR      | 14/10/1998           | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No |
|          |         |                      | <input type="checkbox"/> Yes <input type="checkbox"/> No            |

I hereby claim the benefit under *Title 35, United States Code, § 120* of any United States application(s) or PCT international application(s) designating The United States of America listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in that/those prior application(s) in the manner provided by the first paragraph of *Title 35, United States Code, § 112*, I acknowledge the duty to disclose material information as defined in *Title 37, Code of Federal Regulations, § 1.56* which occurred between the filing date of the prior application(s) and the national or PCT international filing date of this application:

| APPLICATION NUMBER | FILING DATE | STATUS (Patented, Pending or Abandoned) |
|--------------------|-------------|-----------------------------------------|
|                    |             |                                         |
|                    |             |                                         |

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine, or imprisonment, or both, under *Section 1001 of Title 18 of the United States Code*, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

POWER OF ATTORNEY: I (We) hereby appoint as my (our) attorneys, with full powers of substitution and revocation, to prosecute this application and transact all business in the Patent and Trademark Office connected therewith: Allan M. Lowe, Registration Number 19,641; Benjamin J. Hauptman, Registration Number 29,310; Michael G. Gilman, Registration Number 19,114; Kenneth M. Berner, Registration Number 37,093; and Randy A. Noranbrock, Registration Number 42,940.

Send correspondence to: **LOWE HAUPTMAN GILMAN & BERNER, LLP**  
**CUSTOMER NO. 22429**  
 1700 Diagonal Road, Suite 310  
 Alexandria, Virginia 22314


TELEPHONE CALLS TO:  
Allan M. Lowe  
 (703) 684-1111

I hereby authorize the U.S. attorneys and agents named herein to accept and following instructions from CABINET LEGUEN & MAILLET as to any actions to be taken in the U.S. Patent and Trademark Office regarding this application without direct communication between the U.S. attorneys and the undersigned. In the event of a change in the person(s) from whom instructions may be taken, the U.S. attorneys will be so notified by the undersigned.


## DECLARATION FOR PATENT APPLICATION AND APPOINTMENT OF ATTORNEY

Page 2


100

|                                     |                               |                            |                                                                                     |
|-------------------------------------|-------------------------------|----------------------------|-------------------------------------------------------------------------------------|
| Full Name of First or Sole Inventor | <u>Dominique CURET</u>        | Citizenship                | French                                                                              |
| Residence Address - Street          | 38, rue Lariboisiere          | Post Office Address Street |                                                                                     |
| City                                | <u>Thorigne Fouillard</u> FRX | City                       |                                                                                     |
| State or Country                    | France                        | Zip                        | 35235                                                                               |
| State or country                    |                               | Zip                        |                                                                                     |
| DATE                                | 25/06/2001                    | SIGNATURE                  |  |


200

|                              |                        |                            |                                                                                    |
|------------------------------|------------------------|----------------------------|------------------------------------------------------------------------------------|
| Full Name of Second Inventor | <u>Michel VEILLARD</u> | Citizenship                | French                                                                             |
| Residence Address - Street   | 69, rue Mozart         | Post Office Address Street |                                                                                    |
| City                         | <u>Bruz</u> FRX        | City                       |                                                                                    |
| State or Country             | France                 | Zip                        | 35170                                                                              |
| State or country             |                        | Zip                        |                                                                                    |
| DATE                         | 25/06/2001             | SIGNATURE                  |  |


300

|                             |                         |                            |                                                                                      |
|-----------------------------|-------------------------|----------------------------|--------------------------------------------------------------------------------------|
| Full Name of Third Inventor | <u>Germain LOLIVIER</u> | Citizenship                | French                                                                               |
| Residence Address - Street  | 3, square de Tanouarn   | Post Office Address Street |                                                                                      |
| City                        | <u>Rennes</u> FRX       | City                       |                                                                                      |
| State or Country            | France                  | Zip                        | 35700                                                                                |
| State or country            |                         | Zip                        |                                                                                      |
| DATE                        | 25/06/2001              | SIGNATURE                  |  |

400

|                              |                                      |                            |                                                                                      |
|------------------------------|--------------------------------------|----------------------------|--------------------------------------------------------------------------------------|
| Full Name of Fourth Inventor | <u>Therese GARALT</u>                | Citizenship                | French                                                                               |
| Residence Address - Street   | 107, rue F. Benoit                   | Post Office Address Street |                                                                                      |
| City                         | <u>Saint-Jacques de la Lande</u> FRX | City                       |                                                                                      |
| State or Country             | France                               | Zip                        | 35136                                                                                |
| State or country             |                                      | Zip                        |                                                                                      |
| DATE                         | 25/06/2001                           | SIGNATURE                  |  |


500

|                             |                            |                            |                                                                                       |
|-----------------------------|----------------------------|----------------------------|---------------------------------------------------------------------------------------|
| Full Name of Fifth Inventor | <u>Gerard HELLEGOUARCH</u> | Citizenship                | French                                                                                |
| Residence Address - Street  | 33, rue de la Rabine       | Post Office Address Street |                                                                                       |
| City                        | <u>Cesson-Sevigne</u> FRX  | City                       |                                                                                       |
| State or Country            | France                     | Zip                        | 35510                                                                                 |
| State or country            |                            | Zip                        |                                                                                       |
| DATE                        | 25/06/2001                 | SIGNATURE                  |  |


## DECLARATION FOR PATENT APPLICATION AND APPOINTMENT OF ATTORNEY

Page 3


600

|                             |                  |                            |                                                                                    |
|-----------------------------|------------------|----------------------------|------------------------------------------------------------------------------------|
| Full Name of Sixth Inventor | Andre DOUTEAU    | Citizenship                | French                                                                             |
| Residence Address - Street  | 10, rue de Turge | Post Office Address Street |                                                                                    |
| City                        | Chavagne FRX     | City                       |                                                                                    |
| State or Country            | France           | Zip                        | 35310                                                                              |
| DATE                        | 25/06/01         | SIGNATURE                  |  |

700

|                               |                           |                            |                                                                                    |
|-------------------------------|---------------------------|----------------------------|------------------------------------------------------------------------------------|
| Full Name of Seventh Inventor | Stephanie RELIER          | Citizenship                | French                                                                             |
| Residence Address - Street    | 28, square Fernand Labori | Post Office Address Street |                                                                                    |
| City                          | Rennes FRX                | City                       |                                                                                    |
| State or Country              | France                    | Zip                        | 35700                                                                              |
| DATE                          | 26/06/01                  | SIGNATURE                  |  |

800

|                              |                     |                            |                                                                                      |
|------------------------------|---------------------|----------------------------|--------------------------------------------------------------------------------------|
| Full Name of Eighth Inventor | Gerard MADEC        | Citizenship                | French                                                                               |
| Residence Address - Street   | La Brosse           | Post Office Address Street |                                                                                      |
| City                         | Chasne-sur-Ilet FRX | City                       |                                                                                      |
| State or Country             | France              | Zip                        | 35250                                                                                |
| DATE                         | 28/6/01             | SIGNATURE                  |  |

|                             |  |                            |  |
|-----------------------------|--|----------------------------|--|
| Full Name of Ninth Inventor |  | Citizenship                |  |
| Residence Address - Street  |  | Post Office Address Street |  |
| City                        |  | City                       |  |
| State or Country            |  | Zip                        |  |
| DATE                        |  | SIGNATURE                  |  |

|                             |  |                            |  |
|-----------------------------|--|----------------------------|--|
| Full Name of Tenth Inventor |  | Citizenship                |  |
| Residence Address - Street  |  | Post Office Address Street |  |
| City                        |  | City                       |  |
| State or Country            |  | Zip                        |  |
| DATE                        |  | SIGNATURE                  |  |